Using Dali for Protein Structure Comparison

Holm, Liisa

Humana press

2020

Holm , L 2020 , Using Dali for Protein Structure Comparison . in Z Gáspári (ed.) , Structural Bioinformatics : Methods and Protocols . vol. 2112 , Methods in Molecular Biology , vol. 2112 , Humana press , pp. 29-42 . https://doi.org/10.1007/978-1-0716-0270-6_3

<http://hdl.handle.net/10138/328866>

https://doi.org/10.1007/978-1-0716-0270-6_3

unspecified

acceptedVersion

Downloaded from Helda, University of Helsinki institutional repository.

This is an electronic reprint of the original article.

This reprint may differ from the original in pagination and typographic detail.

Please cite the original version.

F

by Springer Nature

Cover page

Liisa Holm

Institute of Biotechnology & Department of Biological Sciences, University of Helsinki, Finland

liisa.holm@helsinki.fi

Running head: Using DALI for protein structure comparison

Abstract

The exponential growth in the number of newly solved protein structures makes correlating and classifying the data an important task. Distance matrix alignment (Dali) is used routinely by crystallographers worldwide to screen the database of known structures for similarity to newly-determined structures. Dali is easily accessible through the web server (<http://ekhidna.biocenter.helsinki.fi/dali>). Alternatively, the program may be downloaded and pairwise comparisons performed locally on Linux computers.

Key Words

classification of protein folds; database searching; distance geometry; pattern recognition; protein structure alignment

Introduction

At the end of 2018, the Protein Data Bank (PDB) contained the structure of 300,000 protein chains. Nearly all proteins have structural similarities to other proteins. General similarities arise from principles of physics and chemistry that limit the number of ways in which a polypeptide chain can fold into a compact globule. Evolutionary relationships result in surprising similarities, which are even stronger than similarity due to convergence caused by physical principles. Comparing 3D structures may reveal biologically interesting similarities that are not detectable by comparing only sequences and may help to infer functional properties of hypothetical proteins. For example, the recent discovery of structural homology and a conserved Cys-Asp-His catalytic triad unified two previously uncharacterized effectors from *Legionella pneumophila* with the cycle inhibiting factors (cif) gene family, leading to mechanistic insights of host manipulation by this pathogenic bacterium [1].

Large proteins can be decomposed into semi-autonomous, globular folding units called domains. Domains are often evolutionarily mobile modules and may carry specific biological functions. Because a common

domain may be surrounded by completely unrelated domains, most structure comparison methods search for local similarities. A structural alignment defines a set of one-to-one correspondences between C α atoms in two proteins. This is analogous to sequence alignment, except that the notion of similarity is much more complex between three-dimensional objects than between linear sequences. A large variety of scoring functions for structural similarity have been proposed [2]. The most important categories are (i) scoring functions based on the root mean square deviation (RMSD) of rigid-body superimposition and (ii) scoring functions allowing flexible superimposition or plastic deformations. Early works based on visual analysis of folds stressed the importance of plastic deformations in the evolution of protein structure. Dali function belongs to the latter category, and it has been shown to yield structural dendrograms that agree well with expert classifications [3-5].

The Dali method is based on a sensitive measure of geometrical similarities defined as a weighted sum of similarities of intramolecular distances [3].

substructures is evaluated using an additive similarity score S of the form:

Equation 1

where i and j label residues, $core$ is the common substructure, and s_{ij} is a similarity measure based on some pairwise relationship, here on the similarity of intramolecular C α -C α distances. Unmatched residues do not contribute to the overall score. For a given functional form of s_{ij} , the largest value of S corresponds to the optimal set of residue equivalences. The similarity measure needs to balance two contradictory requirements: maximizing the number of equivalenced residues and minimizing structural deviations. The use of relative rather than absolute deviations of equivalent distances is tolerant to the cumulative effect of gradual geometrical distortions. In Dali, the residue-pair score s_{ij} has the form:

Equation 2

where the first term of the multiplication is the relative distance difference compared to a similarity threshold t and the second term is an envelope function which downweights pairs in the long distance range. In Dali, the similarity threshold is set to $t = 0.2$. The envelope is a Gaussian function

— where $R_0 = 20$ Å, calibrated on the size of a typical domain. The relative distance difference

——, where d_A and d_B are intramolecular C α -C α distances in structure A and B,

respectively, and their average is —. Inserting the values of the constants, the resulting raw Dali score describing the structural similarity is given by:

Equation 3

$$S = \sum_{i,j \in core} s_{ij} = \sum_{i,j \in core} \frac{1}{1 + \left(\frac{d_A + d_B}{2R_0} \right)^2} \left(1 - \left| \frac{d_A - d_B}{d_A + d_B} \right| \right)^2$$

The residue-pair scores (Figure 1) can get both positive and negative values, therefore the maximum of Equation 3 corresponds to a local alignment. Hydrogen bonded backbone segments in helices and sheets have a distance around 5 Å. Here absolute distance deviations up to 1 Å generate positive scores, while larger deviations incur a steeply increasing penalty. At 10 Å distance, as found between helices or sheets in tertiary contact, a deviation up to 2 Å still contributes positively, and larger deviations incur a mild penalty. The diameter of a typical domain is around 20 Å. Beyond this distance, the score function is relatively insensitive to distance deviations. For example, two conformations of a two-domain structure, which are not superimposable as rigid bodies because of hinge rotation, can be structurally aligned by Dali since the similarity of local structure compensates for the downweighted deviations in interdomain distances.

Figure 1. Pairwise distances contribute a positive score (yellow color) when the relative deviation is less than 20 %. An envelope function damps the contribution of longer distances.

For random pairwise comparison the expected Dali-score (Equation 3) increases with the number of residues in the compared proteins. In order to describe the statistical significance of a pairwise comparison score $S(A,B)$, we use the Z-score defined as

Equation 4

The relation between the mean score m , standard deviation σ and the average length L of two proteins was derived empirically from a large set of random pairs of structures. Fitting a polynomial gave the approximation:

$$\text{Equation 5} \quad m \approx L \left(7.95 - 0.71L + 2.59 \cdot 10^{-4} L^2 - 1.92 \cdot 10^{-6} L^3 \right), \text{ if}$$

For standard deviation, the empirical estimate was $\sigma = \sqrt{m}$. The Z-score is computed for every possible pair of domains, and the highest value is reported as the Z-score of the protein pair [6]. Possible domains are determined by the Puu algorithm (Parser for protein Unfolding Units), which recursively cuts a structure into smaller compact substructures at the weakest interface [7].

Materials

The Dali method is available as a web service at <http://ekhidna.biocenter.helsinki.fi/dali>. The standalone version can be downloaded from <http://ekhidna.biocenter.helsinki.fi/dali/README.html>, which gives instructions for installation. The package contains two Perl wrapper scripts along with installation instructions in the README file as well as source code and sample input/output files. The program is designed to run under Linux. Compiling the source code requires Fortran-90 (e.g. gfortran) and C compilers. openmpi is optional. Standard Perl is required to execute the wrapper scripts. To install the programs, unpack the zip archive in a suitable directory, edit the path to the Dali home directory in the Makefile and follow the instructions.

The installed package contains two Perl scripts:

1. A script `import.pl` which must be used to convert PDB files to internal data format. This script handles the input PDB files which might contain multiple chains, passes them to the DSSP program for extracting the coordinates and defining secondary structure elements, reads the output of DSSP, prepares a hierarchical tree of folding units, and outputs a data file for each chain in the input PDB file (see Note 1).
2. The script `dali.pl` performs pairwise comparisons of a list of query structures to a list of target structures. The lists of query and target structures must be provided by the user (see Note 2).

Methods

3.1 Input file

The input structure must be a PDB format text file. The PDB format consist of records (lines) where the first six characters are a keyword and data follows in fixed-width columns. Dali uses data from the COMPND and ATOM records. Only the first model of an NMR ensemble is read in. The input structure must have

complete backbone atoms (C, CA, N, O), this requirement comes from the DSSP program used to parse PDB files. Though only CA coordinates are used in structural alignment, the DSSP step is necessary because also secondary structure assignments by DSSP are used as input to structure comparison. Chains shorter than 29 amino acids are ignored (see Note 3). The maximum throughput of the web server is 100 - 200 structure database searches per day. To apply the method on a larger number of structures, we advise the use of the standalone version.

3.2 Structure data parsing

The DSSP method [8] is used to parse C α coordinates and to define secondary structure elements from the PDB file. The dsspCMBI implementation of DSSP is included in the standalone package. dsspCMBI is maintained at <ftp://ftp.cmbi.ru.nl/pub/software/dssp/>. The DSSP algorithm defines hydrogen bonds based on the dipole interaction of backbone amide and carbonyl groups. The interaction energy is modelled by a Coulomb potential between partial charges, which leads to a function of the angle and distance of the dipoles. Regular patterns of hydrogen bonds between runs of residues generate turns, helices, bridges, ladders and sheets. Dali uses secondary structure elements (helices, beta strands) to simplify structural alignment. Alignment is further simplified by using a tree of compact substructures to guide alignment identifying first local matches and then solving a combinatorial problem in building up larger clusters of matching substructures. The tree is generated by the Puu program [7]. The underlying physical concept is maximal interactions within each unit and minimal interaction between units (domains). In a simple harmonic approximation, interdomain dynamics is determined by the strength of the interface and the distribution of masses. The most likely domain decomposition involves units with the most correlated

complicated by the possibility that the chain can cross over several times between units. Grouping the residues by solving an eigenvalue problem for the co
dimensional search for all reasonable trial bisections. Recursive bisection yields a tree of putative folding units. Simple physical criteria are used to identify units that could exist by themselves.

3.3 Pairwise comparison

Dali implements four structure alignment algorithms. In the standalone package these are available through the serialcompare / mpicompare programs, though in practice they are invoked through the wrapper script dali.pl.

1. The Soap algorithm [9] is used to align structures with few (see Note 4) secondary structure elements.
C α traces superimposed in 3D space. The minimal surface area between the virtual backbones of two proteins is determined numerically using an iterative triangulation strategy. The first protein is then rotated and translated in space until the